

09/19/00
jc931 U.S. PTO

09-20-00

A

FORM PTO-1082

Express Mail EL 549 326 341 US

PATENT

Atty. Docket No. 31428-1002

Date: September 19, 2000

UTILITY PATENT APPLICATION TRANSMITTAL and FEE TRANSMITTAL

Box PATENT APPLICATION
COMMISSIONER FOR PATENTS
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of:

Inventor(s): Ping YIP
For: METHOD AND DEVICE FOR IDENTIFYING A BIOLOGICAL SAMPLE


Enclosed are:

- ☒ Specification, Claims, and Abstract (34 pages)
☒ 17 Sheet(s) of drawing (☐ formal, ☒ informal)
☐ Form PTO-1595 and an assignment of the invention to: _____ Will follow.
☐ A certified copy of _____ from which priority is claimed in the subject case pursuant to Rule 55b and 35 U.S.C. 119. ☐ Will follow.
☐ An associate Power of Attorney. ☐ Will follow.
☒ A verified statement to establish small entity status under 37 CFR 1.9 and 37 CFR 1.27. ☐ Will follow.
☒ Combined Declaration and Power of Attorney (unsigned). ☐ Will follow.
☐ Information Disclosure Statement, Form PTO-1449, and 2 cited references
☒ Postcard

FOR:	NO. FILED	In Excess	NO. EXTRA	SMALL ENTITY			LARGE ENTITY	
				RATE	FEE		RATE	FEE
BASIC FEE				\$345.00	\$345.00	OR	\$690.00	\$
TOTAL CLAIMS	45	- 20	= 25	x \$ 9.00	\$225.00	OR	x\$ 18.00	\$
INDEF CLAIMS	5	- 3	= 2	x \$ 39.00	\$ 78.00	OR	x\$ 78.00	\$
PRESENTATION OF MULTIPLE DEPENDANT CLAIM				+ \$130.00	\$ 0.00	OR	+ 260.00	\$
TOTAL				\$648.00		OR	TOTAL	\$ 0.00

- ☒ Check Number 72610 in the amount of \$648.00 to cover the filing fee is enclosed.
☐ Check Number _____ in the amount of \$ 0.00 to cover the Assignment Recordation Fee.
☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 02-0410 of Baker & McKenzie.
A duplicate copy of this sheet is enclosed.
☒ Any additional filing fees required under 37 CFR 1.16.
☒ Any patent application processing fees under 37 CFR 1.17.
☐ The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 02-0410. A duplicate copy of this sheet is enclosed.
☐ Any patent application processing fees under 37 CFR 1.17.
☐ The issue fee set in 37 CFR 1.18 at or before mailing of the Notice of Allowance, pursuant to 37 CFR 1.311(b).
☐ Any filing fees under CFR 1.16 for presentation or extra claims.

Respectfully submitted,


Mitchell P. Brook
Registration No. 32,967
c/o BAKER & MCKENZIE
101 West Broadway, 12th Floor
San Diego, California 92101
(619) 236-1441

jc922 U.S. PTO
09/663968
09/19/00

09663968-091900

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE



In re Application of:)	Art Unit: Unknown
Ping YIP)	
)	Examiner: Unknown
Serial No.: TBA)	
)	
Filed: September 19, 2000)	
)	
For: METHOD AND DEVICE FOR)	
IDENTIFYING A BIOLOGICAL)	
SAMPLE)	

San Diego, California 92101
September 19, 2000

BOX PATENT APPLICATION
Assistant Commissioner For Patents
Washington, D.C. 20231


CERTIFICATE OF EXPRESS MAILING

Dear Sir:

“Express Mail” mailing label No. EL 549 326 341 US


Date of Deposit: September 19, 2000

I hereby certify that a Patent Application including the Specification, Abstract, and claims (34 pages), informal drawings (FIGS. 1-33 on 17 pages), Combined Declaration for Patent Application and Power of Attorney (unsigned 2 pages), check in the amount of \$648.00, Utility Patent Application Transmittal and Fee Transmittal (in duplicate), Statement Claiming Small Entity Status, and return postcard are being deposited with the U.S. Postal Service “Express Mail Post Office to the Addressee” service under 37 CFR § 1.10 on the date indicated above and is addressed to Box Patent Application, Commissioner for Patents, Washington, D.C. 20231.


Linda Jonkers-Yocom

Approved for use through 09/30/2000 PTO/SB/10 (1-99)
 Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
 OMB 0651-0031

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

STATEMENT CLAIMING SMALL ENTITY STATUS (37 CFR 1.9(f) & 1.27(c))--SMALL BUSINESS CONCERN		Docket Number (Optional) 31428-1002
Applicant, Patentee, or Identifier: <u>PING YIP</u> Application or Patent No.: <u>TBA</u> Filed or Issued: <u>September 19, 2000</u> Title: <u>METHOD AND DEVICE FOR IDENTIFYING A BIOLOGICAL SAMPLE</u>		
I hereby state that I am <input type="checkbox"/> the owner of the small business concern identified below; <input checked="" type="checkbox"/> an official of the small business concern empowered to act on behalf of the concern identified below:		
NAME OF SMALL BUSINESS CONCERN <u>SEQUENOM, INC.</u>		
ADDRESS OF SMALL BUSINESS CONCERN <u>11555 SORRENTO VALLEY ROAD</u> <u>SAN DIEGO, CALIFORNIA 92121-1331</u>		
I hereby state that the above identified small business concern qualifies as a small business concern as defined in 13 CFR Part 121 for purposes of paying reduced fees to the United States Patent and Trademark Office. Questions related to size standards for a small business concern may be directed to: Small Business Administration, Size Standards Staff, 409 Third Street, SW, Washington, DC 20416.		
I hereby state that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention described in:		
<input checked="" type="checkbox"/> the specification filed herewith with title as listed above <input type="checkbox"/> the application identified above. <input type="checkbox"/> the patent identified above.		
If the rights held by the above identified small business concern are not exclusive, each individual, concern, or organization having rights in the invention must file separate statements as to their status as small entities, and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d), or a nonprofit organization under 37 CFR 1.9(e).		
Each person, concern, or organization having any rights in the invention is listed below: <input checked="" type="checkbox"/> no such person, concern, or organization exists. <input type="checkbox"/> each such person, concern, or organization is listed below		
Separate statements are required from each named person, concern or organization having rights to the invention stating their status as small entities. (37 CFR 1.27)		
I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))		
NAME OF PERSON SIGNING <u>STEVE ZANIBONI</u>		
TITLE OF PERSON IF OTHER THAN OWNER <u>CHIEF FINANCIAL OFFICER</u>		
ADDRESS OF PERSON SIGNING _____		
SIGNATURE <u></u> DATE <u>9.19.00</u>		

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

 1c922 U.S. PTO
 09/663968

09/19/00

00663968 09/19/00

Atty. Dkt. No. 67131428-1002
Express Mail No. EL 549 326 341 US

METHOD AND DEVICE FOR IDENTIFYING A BIOLOGICAL SAMPLE

006T60"396E9360

Inventor: Ping Yip

METHOD AND DEVICE FOR IDENTIFYING A BIOLOGICAL SAMPLE

Priority is claimed to U.S. patent application serial number 09/285,481, filed April 2, 1999, and entitled "Automated Process Line", which is referred to and incorporated herein in its entirety by this reference.

Field Of The Invention

The present invention is in the field of biological identification. More specifically, the present invention relates to identifying a biological sample by analyzing information received from a test instrument.

Background Of The Invention

Advances in the field of genomics are leading to the discovery of new and valuable information regarding genetic processes and relationships. This newly illuminated genetic information is revolutionizing the way medical therapies are advanced, tested, and delivered. As more information is gathered, genetic analysis has the potential to play an integral and central role in developing and delivering medical advancements that will significantly enhance the quality of life.

With the increasing importance and reliance on genetic information, the accurate and reliable collection and processing of genetic data is critical. However, conventional known systems for collecting and processing genetic or DNA data are inadequate to support the informational needs of the genomics community. For example, known DNA collection systems often require substantial human intervention, which undesirably risks inaccuracies associated

with human intervention. Further, the slow pace of such a manual task severely limits the quantity of data that can be collected in a given period of time, which slows needed medical advancements and adds substantially to the cost of data collection.

In a particularly exciting area of genomics, the identification and classification of minute variations in human DNA has been linked with fundamental _____ for a specific individual. For example, the variations are a strong indication of predisposition for a particular disease, drug tolerance, and drug efficiency. The most promising of these minute variations are commonly referred to as Single Nucleotide Polymorphisms (SNPs), which relate to a single base-pair change between a first subject and a second subject. By accurately and fully identifying such SNPs, a health care provider would have a powerful indication of a person's likelihood of succumbing to a particular disease, which drugs will be most effective for that person, and what drug treatment plan will be most beneficial. Armed with such knowledge, the health care provider can assist a person in lowering other risk factors for high-susceptibility diseases. Further, the health care provider can confidently select appropriate drug therapies, a process which is now an iterative, hit or miss process where different drugs and treatment schedules are tried until an effective one is found. Not only is this a waste of limited medical resources, but the time lost in finding an effective therapy can have serious medical consequences for the patient.

In order to fully benefit from the use of SNP data, vast quantities of DNA data must be collected, compared, and analyzed. For example, collecting and identifying the SNP profile for a single human subject requires the collection, identification, and classification of thousands, even tens of thousands of DNA samples. Further, the analysis of the resulting DNA data must be carried out with precision. In making a genetic call, where a composition of a biological sample

is identified, any error in the call may result in detrimentally affecting the medical advice or treatment to a given patient.

Conventional, known systems and processes for collecting and analyzing DNA data are inadequate to timely and efficiently implement a widespread medical program benefiting from
5 SNP information. For example, many known DNA analysis techniques require the use of an operator or technician to monitor and review the DNA data. An operator, even with sufficient training and substantial experience, is still likely to occasionally make a classification error. For example, the operator may incorrectly identify a base-pair, leading to that patient receiving faulty SNP profile. Alternatively, the operator may view the data and decide that the data does not
10 clearly identify any particular base pair. Although such a “no call” may be warranted, it is likely that the operator will make “no-call” decisions when the data actually supports a valid call. In such a manner, the opportunity to more fully profile the patient is lost.

Therefore, there exists a need for a system and process to efficiently and accurately collect and analyze data, such as DNA data.

Summary Of The Invention

It is an object of the present invention to provide an apparatus and process for accurately identifying genetic information. It is another object of the present invention that genetic information be extracted from genetic data in a highly automated manner. Therefore, to
20 overcome the deficiencies in the known conventional systems, a method and apparatus for identifying a biological sample is proposed.

Briefly, the method and system for identifying a biological sample generates a data set indicative of the composition of the biological sample. In a particular example, the data set is DNA spectrometry data received from a mass spectrometer. The data set is denoised, and a

baseline is deleted. Since possible compositions of the biological sample may be known, expected peak areas may be determined. Using the expected peak areas, a residual baseline is generated to further correct the data set. Probable peaks are then identifiable in the corrected data set, which are used to identify the composition of the biological sample. In a disclosed example, statistical methods are employed to determine the probability that a probable peak is an actual peak, not an actual peak, or that the data too inconclusive to call.

Advantageously, the method and system for identifying a biological sample accurately makes composition calls in a highly automated manner. In such a manner, complete SNP profile information, for example, may be collected efficiently. More importantly, the collected data is analyzed with highly accurate results. For example, when a particular composition is called, the result may be relied upon with great confidence. Such confidence is provided by the robust computational process employed, and the highly automatic method of collecting, processing, and analyzing the data set.

These and other features and advantages of the present invention will be appreciated from review of the following detailed description of the invention, along with the accompanying figures in which like reference numerals refer to like parts throughout.

Brief Description Of The Drawings

FIG. 1 is a block diagram showing a system in accordance with the present invention;

FIG. 2 is a flowchart of a method of identifying a biological sample in accordance with the present invention;

FIG. 3 is a graphical representation of data from a mass spectrometer;

FIG. 4 is a diagram of wavelet transformation of mass spectrometry data;

FIG. 5 is a graphical representation of wavelet stage 0 hi data;

FIG. 6 is a graphical representation of stage 0 noise profile;

FIG. 7 is a graphical representation of generating stage noise standard deviations;

FIG. 8 is a graphical representation of applying a threshold to data stages;

5 FIG. 9 is a graphical representation of a sparse data set;

FIG. 10 is a formula for signal shifting;

FIG. 11 is a graphical representation of a wavelet transformation of a denoised and shifted signal;

FIG. 12 is a graphical representation of a denoised and shifted signal;

FIG. 13 is a graphical representation of removing peak sections;

FIG. 14 is a graphical representation of generating a peak free signal ;

FIG. 15 is a block diagram of a method of generating a baseline correction;

FIG. 16 is a graphical representation of a baseline and signal;

FIG. 17 is a graphical representation of a signal with baseline removed;

FIG. 18 is a table showing compressed data;

FIG. 19 is a flowchart of method for compressing data;

FIG. 20 is a graphical representation of mass shifting;

FIG. 21 is a graphical representation of determining peak width;

FIG. 22 is a graphical representation of removing peaks;

20 FIG. 23 is a graphical representation of a signal with peaks removed;

FIG. 24 is a graphical representation of a residual baseline;

FIG. 25 is a graphical representation of a signal with residual baseline removed;

FIG. 26 is a graphical representation of determining peak height;

FIG. 27 is a graphical representation of determining signal-to-noise for each peak;
FIG. 28 is a graphical representation of determining a residual error for each peak;
FIG. 29 is a graphical representation of peak probabilities;
FIG. 30 is a graphical representation of applying an allelic ratio to peak probability;
5 FIG. 31 is a graphical representation of determining peak probability
FIG. 32 is a graphical representation of calling a genotype; and
FIG. 33 is a flowchart showing a statistical procedure for calling a genotype.

Detailed Description Of The Invention

10 In accordance with the present invention, a method and device for identifying a biological sample is provided. Referring now to FIG. 1, an apparatus 10 for identifying a biological sample is disclosed. The apparatus 10 for identifying a biological sample generally comprises a mass spectrometer 15 communicating with a computing device 20. In a preferred embodiment, the mass spectrometer may be a MALDI-TOF mass spectrometer manufactured by Bruker-Franzen Analytik GmbH; however, it will be appreciated that other mass spectrometers can be substituted. The computing device 20 is preferably a general purpose computing device. However, it will be appreciated that the computing device could be alternatively configured, for example, it may be integrated with the mass spectrometer or could be part of a computer in a larger network system.

20 The apparatus 10 for identifying a biological sample may operate as an automated identification system having a robot 25 with a robotic arm 27 configured to deliver a sample plate 29 into a receiving area 31 of the mass spectrometer 15. In such a manner, the sample to be identified may be placed on the plate 29 and automatically received into the mass spectrometer 15. The biological sample is then processed in the mass spectrometer to generate data indicative

mathematical modeling. Wavelet technology provides a basic expansion function which is applied to a data set. Using wavelet decomposition, the data set can be simultaneously analyzed in both the time and frequency domains. Wavelet transformation is the technique of choice in the analysis of data that exhibit complicated time (mass) and frequency domain information, such as MALDI-TOF DNA data. Wavelet transforms as described herein have superior denoising properties as compared to conventional Fourier analysis techniques. Wavelet transformation has proven to be particularly effective in interpreting the inherently noisy MALDI-TOF spectra of DNA samples. In using wavelets, a “small wave” or “scaling function” is used to transform a data set into stages, with each stage representing a frequency component in the data set. Using wavelet transformation, mass spectrometry data can be processed, filtered, and analyzed with sufficient discrimination to be useful for identification of the DNA composition for a biological sample.

Referring again to FIG. 2, the data received in block 40 is denoised in block 45. The denoised data then has a baseline correction applied in block 50. A baseline correction is generally necessary as data coming from the test instrument, in particular a mass spectrometer instrument, has data arranged in a generally exponentially decaying manner. This generally exponential decaying arrangement is not due to the composition of the biological sample, but is a result of the physical properties and characteristics of the test instrument, and other chemicals involved in DNA sample preparation. Accordingly, baseline correction substantially corrects the data to remove a component of the data attributable to the test system, and sample preparation characteristics.

After denoising in block 45 and the baseline correction in block 50, a signal remains which is generally indicative of the composition of the biological sample. However, due to the

high data 84 and stage 1 low data 85. In a similar manner, the stage 1 low data 85 is used as an input to be transformed into stage 2 high data 86 and stage 2 low data 87. The transformation is continued until no more useful information can be derived by further wavelet transformation. For example, in the preferred embodiment a 24-point wavelet is used. More particularly a wavelet commonly referred to as the Daubechies 24 is used to decompose the raw data. However, it will be appreciated that other wavelets can be used for the wavelet transformation. Since each stage in a wavelet transformation has one-half the data points of the previous stage, the wavelet transformation can be continued until the stage n low data 89 has around 50 points. Accordingly, the stage n high 88 would contain about 100 data points. Since the preferred wavelet is 24 points long, little data or information can be derived by continuing the wavelet transformation on a data set of around 50 points.

FIG. 5 shows an example of stage 0 high data 95. Since stage 0 high data 95 is generally indicative of the highest frequencies in the mass spectrometry data, stage 0 high data 95 will closely relate to the quantity of high frequency noise in the mass spectrometry data. In FIG. 6, an exponential fitting formula has been applied to the stage 0 high data 95 to generate a stage 0 noise profile 97. In particular, the exponential fitting formula is in the format $A_0 + A_1 \text{EXP}(-A_2 m)$. It will be appreciated that other expediential fitting formulas or other types of curve fits may be used.

Referring now to FIG. 7, noise profiles for the other high stages are determined. Since the later data points in each stage will likely be representative of the level of noise in each stage, only the later data points in each stage are used to generate a standard deviation figure that is representative of the noise content in that particular stage. More particularly, in generating the noise profile for each remaining stage, only the last five percent of the data points in each stage

are analyzed to determine a standard deviation number. It will be appreciated that other numbers of points, or alternative methods could be used to generate such a standard deviation figure.

The standard deviation number for each stage is used with the stage 0 noise profile (the exponential curve) 97 to generate a scaled noise profile for each stage. For example, FIG. 7 shows that stage 1 high data 98 has stage 1 high data 103 with the last five percent of the data points represented by area 99. The points in area 99 are evaluated to determine a standard deviation number indicative of the noise content in stage 1 high data 103. The standard deviation number is then used with the stage 0 noise profile 97 to generate a stage 1 noise profile.

In a similar manner, stage 2 high 100 has stage 2 high data 104 with the last five percent of points represented by area 101. The data points in area 101 are then used to calculate a standard deviation number which is then used to scale the stage 0 noise profile 97 to generate a noise profile for stage 2 data. This same process is continued for each of the stage high data as shown by the stage n high 105. For stage n high 105, stage n high data 108 has the last five percent of data points indicated in area 106. The data points in area 106 are used to determine a standard deviation number for stage n. The stage n standard deviation number is then used with the stage 0 noise profile 97 to generate a noise profile for stage n. Accordingly, each of the high data stages has a noise profile.

FIG. 8 shows how the noise profile is applied to the data in each stage. Generally, the noise profile is used to generate a threshold which is applied to the data in each stage. Since the noise profile is already scaled to adjust for the noise content of each stage, calculating a threshold permits further adjustment to tune the quantity of noise removed. Wavelet coefficients

below the threshold are ignored while those above the threshold are retained. Accordingly, the remaining data has a substantial portion of the noise content removed.

Due to the characteristics of wavelet transformation, the lower stages, such as stage 0 and 1, will have more noise content than the later stages such as stage 2 or stage n. Indeed, stage n low data is likely to have little noise at all. Therefore, in a preferred embodiment the noise profiles are applied more aggressively in the lower stages and less aggressively in the later stages. For example, FIG. 8 shows that stage 0 high threshold is determined by multiplying the stage 0 noise profile by a factor of four. In such a manner, significant numbers of data points in stage 0 high data 95 will be below the threshold and therefore eliminated. Stage 1 high threshold 112 is set at two times the noise profile for the stage 1 high data, and stage 2 high threshold 114 is set equal to the noise profile for stage 2 high. Following this geometric progression, stage n high threshold 116 is therefore determined by scaling the noise profile for each respective stage n high by a factor equal to $(1/2^{n-2})$. It will be appreciated that other factors may be applied to scale the noise profile for each stage. For example, the noise profile may be scaled more or less aggressively to accommodate specific systemic characteristics or sample compositions. As indicated above, stage n low data does not have a noise profile applied as stage n low data 118 is assumed to have little or no noise content. After the scaled noise profiles have been applied to each high data stage, the mass spectrometry data 70 has been denoised and is ready for further processing. A wavelet transformation of the denoised signal results in the sparse data set 120 as shown in FIG. 9.

Referring again to FIG. 2, the mass spectrometry data received in block 40 has been denoised in block 45 and is now passed to block 50 for baseline correction. Before performing baseline correction, the artifacts introduced by the wavelet transformation procedure are

preferably removed. Wavelet transformation results vary slightly depending upon which point of the wavelet is used as a starting point. For example, the preferred embodiment uses the 24-point Daubechies-24 wavelet. By starting the transformation at the 0 point of the wavelet, a slightly different result will be obtained than if starting at points 1 or 2 of the wavelet. Therefore, the denoised data is transformed using every available possible starting point, with the results averaged to determine a final denoised and shifted signal. For example, FIG. 10 shows that the wavelet coefficient is applied 24 different times and then the results averaged to generate the final data set. It will be appreciated that other techniques may be used to accommodate the slight error introduced due to wavelet shifting.

The formula 125 is generally indicated in FIG. 10. Once the signal has been denoised and shifted, a denoised and shifted signal 130 is generated as shown in FIG. 12. FIG. 11 shows an example of the wavelet coefficient 135 data set from the denoised and shifted signal 130.

FIG. 13 shows that putative peak areas 145, 147, and 149 are located in the denoised and shifted signal 150. The putative peak areas are systematically identified by taking a moving average along the signal 150 and identifying sections of the signal 150 which exceed a threshold related to the moving average. It will be appreciated that other methods can be used to identify putative peak areas in the signal 150.

Putative peak areas 145, 147 and 149 are removed from the signal 150 to create a peak-free signal 155 as shown in FIG. 14. The peak-free signal 155 is further analyzed to identify remaining minimum values 157, and the remaining minimum values 157 are connected to generate the peak-free signal 155.

FIG. 15 shows a process of using the peak-free signal 155 to generate a baseline 170 as shown in FIG. 16. As shown in block 162, a wavelet transformation is performed on the peak-

free signal 155. All the stages from the wavelet transformation are eliminated in block 164 except for the n low stage. The n low stage will generally indicate the lowest frequency component of the peak-free signal 155 and therefore will generally indicate the system exponential characteristics. Block 166 shows that a signal is reconstructed from the n low coefficients and the baseline signal 170 is generated in block 168.

FIG. 16 shows a denoised and shifted data signal 172 positioned adjacent a correction baseline 170. The baseline correction 170 is subtracted from the denoised and shifted signal 172 to generate a signal 175 having a baseline correction applied as shown in FIG. 17. Although such a denoised, shifted, and corrected signal is sufficient for most identification purposes, the putative peaks in signal 175 are not identifiable with sufficient accuracy or confidence to call the DNA composition of a biological sample.

Referring again to FIG. 2, the data from the baseline correction 50 is now compressed in block 55, the compression technique used in a preferred embodiment is detailed in FIG. 18. In FIG. 18 the data in the baseline corrected data is presented in an array format 182 with x-axis points 183 having an associated data value 184. The x-axis is indexed by the non-zero wavelet coefficients, and the associated value is the value of the wavelet coefficient. In the illustrated data example in table 182, the maximum value 184 is indicated to be 1000. Although a particularly advantageous compression technique for mass spectrometry data is shown, it will be appreciated that other compression techniques can be used. Although not preferred, the data may also be stored without compression.

In compressing the data according to a preferred embodiment, an intermediate format 186 is generated. The intermediate format 186 generally comprises a real number having a whole number portion 188 and a decimal portion 190. The whole number portion is the x-axis point

183 while the decimal portion is the value data 184 divided by the maximum data value. For example, in the data 182 a data value “25” is indicated at x-axis point “100”. The intermediate value for this data point would be “100.025”.

From the intermediate compressed data 186 the final compressed data 195 is generated.

5 The first point of the intermediate data file becomes the starting point for the compressed data. Thereafter each data point in the compressed data 195 is calculated as follows: the whole number portion (left of the decimal) is replaced by the difference between the current and the last whole number. The remainder (right of the decimal) remains intact. For example, the starting point of the compressed data 195 is shown to be the same as the intermediate data point which is “100.025”. The comparison between the first intermediate data point “100.025” and the second intermediate data point “150.220” is “50.220”. Therefore, “50.220” becomes the second point of the compressed data 195. In a similar manner, the second intermediate point is “150.220” and the third intermediate data point is “500.0001”. Therefore, the third compressed data becomes “350.000”. The calculation for determining compressed data points is continued until the entire array of data points is converted to a single array of real numbers.

FIG. 19 generally describes the method of compressing mass spectrometry data, showing that the data file in block 201 is presented as an array of coefficients in block 202. The data starting point and maximum is determined as shown in block 203, and the intermediate real numbers are calculated in block 204 as described above. With the intermediate data points generated, the compressed data is generated in block 205. The described compression method is highly advantageous and efficient for compressing data sets such as a processed data set from a mass spectrometry instrument. The method is particularly useful for data, such as mass spectrometry data, that uses large numbers and has been processed to have occasional lengthy

gaps in x-axis data. Accordingly, an x-y data array for processed mass spectrometry data may be stored with an effective compression rate of 10x or more. Although the compression technique is applied to mass spectrometry data, it will be appreciated that the method may also advantageously be applied to other data sets.

5 Referring again to FIG. 2, peak heights are now determined in block 60. The first step in determining peak height is illustrated in FIG. 20 where the signal 210 is shifted left or right to correspond with the position of expected peaks. As the set of possible compositions in the biological sample is known before the mass spectrometry data is generated, the possible positioning of expected peaks is already known. These possible peaks are referred to as expected peaks, such as expected peaks 212, 214, and 216. Due to calibration or other errors in the test instrument data, the entire signal may be shifted left or right from its actual position, therefore, putative peaks located in the signal, such as putative peaks 218, 222, and 224 may be compared to the expected peaks 212, 214, and 216, respectively. The entire signal is then shifted such that the putative peaks align more closely with the expected peaks.

10
15
20 Once the putative peaks have been shifted to match expected peaks, the strongest putative peak is identified in FIG. 21. In a preferred embodiment, the strongest peak is calculated as a combination of analyzing both the overall peak height and area beneath the peak. For example, a moderately high but wide peak would be stronger than a very high peak that is extremely narrow. With the strongest putative peak identified, such as putative peak 225, a Gaussian 228 curve is fit to the peak 225. Once the Gaussian is fit, the width (W) of the Gaussian is determined and will be used as the peak width for future calculations.

As generally addressed above, the denoised, shifted, and baseline-corrected signal is not sufficiently processed for confidently calling the DNA composition of the biological sample.

For example, although the baseline has generally been removed, there are still residual baseline effects present. These residual baseline effects are therefore removed to increase the accuracy and confidence in making identifications.

To remove the residual baseline effects, FIG. 22 shows that the putative peaks 218, 222, and 224 are removed from the baseline corrected signal. The peaks are removed by identifying a center line 230, 232, and 234 of the putative peaks 218, 222, and 224, respectively and removing an area both to the left and to the right of the identified center line. For each putative peak, an area equal to twice the width (W) of the Gaussian is removed from the left of the center line, while an area equivalent to 50 daltons is removed from the right of the center line. It has been found that the area representing 50 daltons is adequate to sufficiently remove the effect of salt adducts which may be associated with an actual peak. Such adducts appear to the right of an actual peak and are a natural effect from the chemistry involved in acquiring a mass spectrum. Although a 50 Dalton buffer has been selected, it will be appreciated that other ranges or methods can be used to reduce or eliminate adduct effects.

The peaks are removed and remaining minima 247 located as shown in FIG. 23 with the minima 247 connected to create signal 245. A quartic polynomial is applied to signal 245 to generate a residual baseline 250 as shown in FIG. 24. The residual baseline 250 is subtracted from the signal 225 to generate the final signal 255 as indicated in FIG. 25. Although the residual baseline is the result of a quartic fit to signal 245, it will be appreciated that other techniques can be used to smooth or fit the residual baseline.

To determine peak height, as shown in FIG. 26, a Gaussian such as Gaussian 266, 268, and 270 is fit to each of the peaks, such as peaks 260, 262, and 264, respectively. Accordingly, the height of the Gaussian is determined as height 272, 274, and 276. Once the height of each

Gaussian peak is determined, then the method of identifying a biological compound 35 can move into the genotyping phase 65 as shown in FIG. 2.

An indication of the confidence that each putative peak is an actual peak can be discerned by calculating a signal-to-noise ratio for each putative peak. Accordingly, putative peaks with a strong signal-to-noise ratio are generally more likely to be an actual peak than a putative peak with a lower signal-to-noise ratio. As described above and shown in FIG. 27, the height of each peak, such as height 272, 274, and 276, is determined for each peak, with the height being an indicator of signal strength for each peak. The noise profile, such as noise profile 97, is extrapolated into noise profile 280 across the identified peaks. At the center line of each of the peaks, a noise value is determined, such as noise value 282, 283, and 284. With a signal values and a noise values generated, signal-to-noise ratios can be calculated for each peak. For example, the signal-to-noise ratio for the first peak in FIG. 27 would be calculated as signal value 272 divided by noise value 282, and in a similar manner the signal-to-noise ratio of the middle peak in FIG. 27 would be determined as signal 274 divided by noise value 283.

Although the signal-to-noise ratio is generally a useful indicator of the presence of an actual peak, further processing has been found to increase the confidence by which a sample can be identified. For example, the signal-to-noise ratio for each peak in the preferred embodiment is preferably adjusted by the goodness of fit between a Gaussian and each putative peak. It is a characteristic of a mass spectrometer that sample material is detected in a manner that generally complies with a normal distribution. Accordingly, greater confidence will be associated with a putative signal having a Gaussian shape than a signal that has a less normal distribution. The error resulting from having a non-Gaussian shape can be referred to as a “residual error”.

Referring to FIG. 28, a residual error is calculated by taking a root mean square calculation between the Gaussian 293 and the putative peak 290 in the data signal. The calculation is performed on data within one width on either side of a center line of the Gaussian. The residual error is calculated as:

$$\frac{\sqrt{(G - R)^2}}{N} \quad \text{where } G \text{ is the Gaussian signal value, } R \text{ is the putative peak value, and}$$

N is the number of points from $-W$ to $+W$. The calculated residual error is used to generate an adjusted signal-to-noise ratio, as described below.

An adjusted signal noise ratio is calculated for each putative peak using the formula $(S/N) * \text{EXP}^{(-.1 * R)}$, where S/N is the signal-to-noise ratio, and R is the residual error determined above. Although the preferred embodiment calculates an adjusted signal-to-noise ratio using a residual error for each peak, it will be appreciated that other techniques can be used to account for the goodness of fit between the Gaussian and the actual signal.

Referring now to FIG. 29, a probability is determined that a putative peak is an actual peak. In making the determination of peak probability, a probability profile 300 is generated where the adjusted signal-to-noise ratio is the x-axis and the probability is the y-axis. Probability is necessarily in the range between a 0% probability and a 100% probability, which is indicated as 1. Generally, the higher the adjusted signal-to-noise ratio, the greater the confidence that a putative peak is an actual peak.

At some target value for the adjusted signal-to-noise, it has been found that the probability is 100% that the putative peak is an actual peak and can confidently be used to identify the DNA composition of a biological sample. However, the target value of adjusted signal-to-noise ratio where the probability is assumed to be 100% is a variable parameter which is to be set according to application specific criteria. For example, the target signal-to-noise ratio

allelic ratios between 10% and 30%, the allelic penalty chart 315 is used to determine a penalty 319, which is multiplied by the peak probability determined in FIG. 29 to determine a final peak probability. Although the preferred embodiment incorporates an allelic ratio penalty to account for a possible chemistry error, it will be appreciated that other techniques may be used. Similar
5 treatment will be applied to the other peaks.

With the peak probability of each peak determined, the statistical probability for various composition components may be determined. As an example, in order to determine the probability of each of three possible combinations of two peaks, -- peak G, peak C and combinations GG, CC and GC. FIG. 31 shows an example where a most probable peak 325 is determined to have a final peak probability of 90%. Peak 325 is positioned such that it represents a G component in the biological sample. Accordingly, it can be maintained that there is a 90% probability that G exists in the biological sample. Also in the example shown in FIG. 31, the second highest probability is peak 330 which has a peak probability of 20%. Peak 330 is at a position associated with a C composition. Accordingly, it can be maintained that there is a 20% probability that C exists in the biological sample.

With the probability of G existing (90%) and the probability of C existing (20%) as a starting point, the probability of combinations of G and C existing can be calculated. For example, FIG. 31 indicates that the probability of GG existing 329 is calculated as 72%. This is calculated as the probability of GG is equal to the probability of G existing (90%) multiplied by
20 the probability of C not existing (100% -20%). So if the probability of G existing is 90% and the probability of C not existing is 80%, the probability of GG is 72%.

In a similar manner, the probability of CC existing is equivalent to the probability of C existing (20%) multiplied by the probability of G not existing (100% - 90%). As shown in

FIG. 31, the probability of C existing is 20% while the probability of G not existing is 10%, so therefore the probability of CC is only 2%. Finally, the probability of GC existing is equal to the probability of G existing (90%) multiplied by the probability of C existing (20%). So if the probability of G existing is 90% and the probability of C existing is 20%, the probability of GC existing is 18%. In summary form, then, the probability of the composition of the biological sample is:

probability of GG: 72%;
probability of GC: 18%; and
probability of CC: 2%.

Once the probabilities of each of the possible combinations has been determined, FIG. 32 is used to decide whether or not sufficient confidence exists to call the genotype. FIG. 32 shows a call chart 335 which has an x-axis 337 which is the ratio of the highest combination probability to the second highest combination probability. The y-axis 339 simply indicates whether the ratio is sufficiently high to justify calling the genotype. The value of the ratio may be indicated by M 340. The value of M is set depending upon trial data, sample composition, and the ability to accept error. For example, the value M may be set relatively high, such as to a value 4 so that the highest probability must be at least four times greater than the second highest probability before confidence is established to call a genotype. However, if a certain level of error may be acceptable, the value of M may be set to a more aggressive value, such as to 3, so that the ratio between the highest and second highest probabilities needs to be only a ratio of 3 or higher. Of course, moderate value may be selected for M when a moderate risk can be accepted. Using the example of FIG. 31, where the probability of GG was 72% and the probability of GC was 18%, the ratio between 72% and 18% is 4.0, therefore, whether M is set to 3, 3.5, or 4, the system

would call the genotype as GG. Although the preferred embodiment uses a ratio between the two highest peak probabilities to determine if a genotype confidently can be called, it will be appreciated that other methods may be substituted. It will also be appreciated that the above techniques may be used for calculating probabilities and choosing genotypes (or more general DNA patterns) consisting of combinations of more than two peaks.

Referring now to FIG. 32, a flow chart is shown generally defining the process of statistically calling genotype described above. In FIG. 32 block 402 shows that the height of each peak is determined and that in block 404 a noise profile is extrapolated for each peak. The signal is determined from the height of each peak in block 406 and the noise for each peak is determined using the noise profile in block 408. In block 410, the signal-to-noise ratio is calculated for each peak. To account for a non-Gaussian peak shape, a residual error is determined in block 412 and an adjusted signal-to-noise ratio is calculated in block 414. Block 416 shows that a probability profile is developed, with the probability of each peak existing found in block 418. An allelic penalty may be applied in block 420, with the allelic penalty applied to the adjusted peak probability in block 422. The probability of each combination of components is calculated in block 424 with the ratio between the two highest probabilities being determined in block 426. If the ratio of probabilities exceeds a threshold value then the genotype is called in block 428.

One skilled in the art will appreciate that the present invention can be practiced by other than the preferred embodiments which are presented in this description for purposes of illustration and not of limitation, and the present invention is limited only by the claims which follow. It is noted that equivalents for the particular embodiments discussed in this description may practice the invention as well.

What is claimed is:

1. A method for identifying a biological sample, comprising:
generating a data set indicative of the composition of the biological sample;
denoising the data set to generate denoised data;
5 deleting the baseline from the denoised data to generate an intermediate data set;
defining putative peaks for the biological sample;
using the putative peaks to generate a residual baseline;
removing the residual baseline from the intermediate data set to generate a
corrected data set;
10 locating, responsive to removing the residual baseline, a probable peak in the
corrected data set; and
identifying, using the located probable peak, the biological sample.
2. The method according to claim 1 wherein the data set is a spectrometry data set.
3. The method according to claim 1 wherein the data set is generated by a mass
15 spectrometer.
4. The method according to claim 1 wherein denoising the data set includes
20 generating a noise profile for the data set.
5. The method according to claim 1 wherein denoising the data set includes
transforming the data set using wavelet technology into a series of stages.

6. The method according to claim 5 further including generating a noise profile for stage 0.

7. The method according to claim 6 further including generating a noise profile for other stages.

8. The method according to claim 7 wherein the noise profile for each of the other stages is the noise profile for stage 0 scaled by a scaling factor.

9. The method according to claim 8 wherein the scaling factor is derived from the end portion of each of the other stages, respectively.

10. The method according to claim 5 further including applying a threshold to selected stages, the threshold being derived from the noise profile.

11. The method according to claim 10 wherein the threshold is scaled by a threshold factor before being applied to the selected stages.

12. The method according to claim 7 wherein the threshold factor is selected so that higher stages of data are filtered less than lower stages.

13. The method according to claim 5 further including generating a sparse data set indicative of the denoised data.

14. The method according to claim 5 further including shifting the denoised data to
5 account for variations due to a starting value for the wavelet transformation.

15. The method according to claim 1 wherein correcting the baseline further includes generating a moving average of the denoised data set.

16. The method according to claim 15 wherein the moving average is used to find
10 peak sections in the denoised data set.

17. The method according to claim 16 wherein the peak sections are removed from
the denoised data set.

18. The method according to claim 17 further including generating a baseline
15 correction.

19. The method according to claim 1 further including compressing the intermediate
20 data set, the intermediate data set having a plurality of data values associated with respective addresses.

20. The method according to claim 19 wherein a compressed data value is a real number that includes a whole portion representing the difference between two addresses.

21. The method according to claim 19 wherein a compressed data value is a real number that includes a decimal portion representing the difference between a maximum value of all the data values and a value at a particular address.

22. The method according to claim 1 further including performing a mass shift based on the position of the putative peaks.

23. The method according to claim 1 wherein generating the residual baseline includes deleting an area around each peak in the intermediate data.

24. The method according to claim 23 wherein the area deleted is derived from a determined width of a peak.

25. The method according to claim 23 wherein the residual baseline is derived from data remaining in the intermediate data after the peaks have been removed.

26. The method according to claim 23 wherein generating the residual baseline includes fitting a quartic polynomial to the data remaining in the intermediate data after the peaks have been removed.

27. The method according to claim 1 wherein the probable peak is located by fitting a Gaussian curve to a peak area in the corrected data set.

28. The method according to claim 1 wherein the identifying step includes using a generated noise profile to calculate the signal-to-noise ratio for the probable peak.

29. The method according to claim 28 wherein a residual peak error is calculated by comparing the probable peak to a Gaussian curve.

30. The method according to claim 29 wherein the residual peak error is used to adjust the signal-to-noise ratio to generate an adjusted signal-to-noise ratio.

31. The method according to claim 1 wherein the identifying step includes deriving a peak probability for the probable peak.

32. The method according to claim 31 wherein the peak probability is derived using the signal-to-noise ratio.

33. The method according to claim 31 wherein the peak probability is derived by using an allelic ratio, the allelic ration being a comparison of two peak heights indicated in the corrected data.

34. The method according to claim 1 wherein the identifying step includes calculating a peak probability that a probable peak in the corrected data is a peak indicating composition of the biological sample.

35. The method according to claim 34 wherein peak probability is calculated for each of a plurality of probable peaks in the corrected data.

36. The method according to claim 35 wherein a highest probability is compared to a second-highest probability to generate a calling ratio.

37. The method according to claim 36 wherein the calling ratio is used to determine if the composition of the biological sample will be called.

38. A system for identifying a biological sample, the system comprising:
an instrument receiving the biological sample and generating a data set indicative of the composition of the biological sample;

a computer communicating to the instrument and configured to receive the generated data set, the computer performing the method of:

denoising the data set to generate denoised data;

deleting the baseline from the denoised data to generate an intermediate data set;

defining putative peaks for the biological sample;

using the putative peaks to generate a residual baseline;

removing the residual baseline from the intermediate data set to generate a corrected data set;

locating, responsive to removing the residual baseline, a probable peak in the corrected data set; and

5 identifying, using the located probable peak, the biological sample.

39. The system according to claim 38 wherein the computer is integral to the instrument.

40. A machine readable program operating on a computing device, the computing device being configured to receive a data set indicating composition of a biological sample, the program implement the steps of:

denoising the data set to generate denoised data;

deleting the baseline from the denoised data to generate an intermediate data set;

defining putative peaks for the biological sample;

using the putative peaks to generate a residual baseline;

removing the residual baseline from the intermediate data set to generate a corrected data set;

locating, responsive to removing the residual baseline, a probable peak in the corrected data set; and

identifying, using the located probable peak, the biological sample.

41. A system for identifying a component of a DNA sample, comprising:

a mass spectrometer receiving the DNA sample and generating a data set indicative of the composition of the DNA sample;

a computing device configured to receive the data set, the computing device implementing the method comprising:

- 5 denoising the data set to generate denoised data;
- removing sufficiently the baseline from the denoised data to generate a corrected data set;
- locating a probable peak in the corrected data set; and
- identifying, using the located probable peak, a component in the composition of the DNA sample.
- 10

42. The system according to claim 41, where the method further includes using a statistical methodology to determine if the located probable peak is an actual peak.

15 43. The system according to claim 41, where the method further includes determining whether the probability of the actual peak existing is sufficiently high to call the component of the DNA sample, and if the probability is not sufficiently high, then the method does not call the component.

20 44. The system according to claim 43, where the percentage of correctly called components is about 100 percent.

45. A system for identifying a component in a biological sample, comprising:

an instrument receiving the biological sample and generating a data set indicative of the component in the biological sample;

a computing device receiving the data set and performing the steps of:

5 generating corrected data by processing the data set to remove noise due to
system and chemical reaction characteristics, the corrected data set having putative peak
areas;

defining the position of expected peaks using known possible peak areas from the biological sample;

shifting the corrected data set to more closely align the putative peaks to the expected peaks;

calculating the probability that the putative peaks in the shifted data set are actual peaks;

calling the composition of the biological sample responsive to the calculated probability.

METHOD AND DEVICE FOR IDENTIFYING A BIOLOGICAL SAMPLE

ABSTRACT

5 The method and system for identifying a biological sample generates a data set indicative of the composition of the biological sample. In a particular example, the data set is DNA spectrometry data received from a mass spectrometer. The data set is denoised, and a baseline is deleted. Since possible compositions of the biological sample may be known, expected peak areas may be determined. Using the expected peak areas, a residual baseline is generated to
10 further correct the data set. Probable peaks are then identifiable in the corrected data set, which are used to identify the composition of the biological sample. In a disclosed example, statistical methods are employed to determine the probability that a probable peak is an actual peak, not an actual peak, or that the data too inconclusive to call.

10
↓





FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

Exp fitting
 $a_0 + a_1 \exp(-a_2 m)$

005T60" 896E9960






FIG. 7

Stage 0 - Hi




Threshold 0=4XNoiseProfile

Stage 1 - Hi




Threshold 1=2XNoiseProfile

Stage 2 - Hi



Threshold 2=1XNoiseProfile

Stage n - Hi



Threshold $n=(1/2^{n-2})XNoiseProfile$

Stage n - Lo




FIG. 8

120
✓




FIG 9

$$\text{Signal (t)} = \frac{(\text{Start 0(t)} + \text{Start 1(t)} + \text{Start 2 (t)} \dots + \text{Start 23 (t)})}{24}$$

FIG. 10 - SHIFT SIGNAL TO ACCOUNT FOR VARIATIONS DUE TO STARTING POINT




FIG. 11

005760" 005760" 005760" 005760"




FIG 12




FIG. 13 - TAKE A MOVING AVERAGE, REMOVE SECTIONS EXCEDING A THRESHOLD




FIG. 14 - FIND MINIMA IN REMAINING SIGNALS AND CONNECT TO FORM A PEAK FREE SIGNAL




FIG. 15 - GENERATE BASELINE CORRECTION




FIG. 16




FIG. 17

005760" 896E9960

NON-0 COEFFICIENTS	VALUE	INTERMEDIATE	RELATIVE
100	25	100.025	100.025
150	220	150.220	50.220
500	.1	500.0001	350.0001
10,050	800	10,050.8	9550.8
10,075	890	10,075.89	25.89
11,125	910	11,125.91	150.91
12,100	1000 (MAX)	12,100.99999	975.99999
13,250	940	13,250.94	1150.94

Handwritten annotations: 183 (pointing to NON-0 COEFFICIENTS), 182 (pointing to VALUE), 184 (pointing to 25), 185 (pointing to 220), 186 (pointing to 100.025), 187 (pointing to 50.220), 188 (pointing to 350.0001), 189 (pointing to 9550.8), 190 (pointing to 25.89), 191 (pointing to 150.91), 192 (pointing to 975.99999), 193 (pointing to 1150.94).

FIG. 18




FIG. 19




FIG. 20







FIG. 21



005150-2265950




FIG. 25




FIG. 26

006T60" 896E9960




FIG. 27






FIG. 28



329

PROBABILITY OF GG EXISTING:

$$\begin{aligned} P(GG) &= P(G) * P(1-C) \\ &= 90\% * (100\% - 20\%) \\ &= 90\% * 80\% \\ &= 72\% \end{aligned}$$

331

PROBABILITY OF CC EXISTING:

$$\begin{aligned} P(CC) &= P(C) * P(1-G) \\ &= 20\% * (100\% - 90\%) \\ &= 20\% * 10\% \\ &= 2\% \end{aligned}$$

333

PROBABILITY OF GC EXISTING:

$$\begin{aligned} P(GC) &= P(G) * P(C) \\ &= 90\% * 20\% \\ &= 18\% \end{aligned}$$




FIG. 31

006T60" 886E9950

call
339 →

No call




FIG. 32

005T60" 895E9960




FIG. 33.

COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY

(Includes Reference to PCT International Applications)

ATTORNEY DOCKET NUMBER

31428-1002

As a below named inventor, I (we) hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METHOD AND DEVICE FOR IDENTIFYING A BIOLOGICAL SAMPLE

the specification of which (check only one item below):

☒ is attached hereto.

☐ was filed as United States application

Serial No. _____

on _____

and was amended

on _____ (if applicable)

☐ was filed as PCT international application

Number _____

on _____

and was amended under PCT Article 19

on _____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 or §356 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America, listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

PRIOR FOREIGN/PCT APPLICATION(S) AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. 119:

COUNTRY (if PCT, indicate "PCT")	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 USC 119	
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO

Combined Declaration For Patent Application and Power of Attorney (Continued) (Includes Reference to PCT International Applications)				ATTORNEY DOCKET NUMBER 31428-1002	
I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56 which became available between the filing date of the prior application(s) and the national or PCT international filing date of this application:					
PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. 120:					
U.S. APPLICATIONS				STATUS (Check one)	
U.S. APPLICATION NUMBER	U.S. FILING DATE		PATENTED	PENDING	ABANDONED
09/285,481	April 2, 1999			X	
PCT APPLICATIONS DESIGNATING THE U.S.					
PCT APPLICATION NO.	PCT FILING DATE	U.S. SERIAL NUMBERS ASSIGNED (if any)			
POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: MITCHELL P. BROOK, Reg. No. 32,967, DAVID I. ROCHE, Reg. No. 30,767, ANTOINETTE F. KONSKI, Reg. No. 34,202, JOHN G. FLAIM, Reg. No. 37,323, and PETER R. MARTINEZ, Reg. No. 42,845, all attorneys with the firm of BAKER & MCKENZIE, which has an office address at 101 West Broadway, San Diego, CA 92101-3890.					
Send Correspondence to: Mitchell P. Brook, Esq. BAKER & MCKENZIE 101 West Broadway, 12th Floor San Diego, CA 92101-3890				Direct Telephone Calls to: (name and telephone number) Mitchell P. Brook (619) 236-1441	
201	FULL NAME OF INVENTOR	FAMILY NAME YIP	FIRST GIVEN NAME Ping	SECOND GIVEN NAME	
	RESIDENCE & CITIZENSHIP	CITY San Diego	STATE OR FOREIGN COUNTRY California	COUNTRY OF CITIZENSHIP USA	
	POST OFFICE ADDRESS	POST OFFICE ADDRESS 3641 Coley Avenue	CITY San Diego	STATE & ZIP CODE/COUNTRY California, 92116 USA	
202	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME	
	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP	
	POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY	
<input type="checkbox"/> Additional inventors are being named on the 1 supplemental Additional Inventor(s) sheets(s) attached hereto.					
I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.					
SIGNATURE OF INVENTOR 201			SIGNATURE OF INVENTOR 202		
DATE			DATE		